

ZKSoftware
The Advanced Biometric Solution



SC102/3



SC202/3



SC302/3



SC402/3

ZKSoftware
RFID
Access Control
The Bright
Star
of Security



SC102/3



SC202/3

Technical Specifications - SC102/202/302/402

- CPU: 32bit embedded RISC
- Capacity: 10000 card handle, 30000 logs
- Verified by: Card, Password+ Card, Pass word
- Reader interface/Data format: embedded 10cm proximity reader/26 bit wiegand. External carder reader interface/26 bit wiegand
- Access control function: 50 time zones, 5 groups, 10 combinations, support many cards access, 10A/12VDC relay switch volume or voltage output
- Alarm function: tamper alarm, threaten alarm, unlock illegally alarm, not block alarm. External alarmed speaker, alarmed light or alarm host connectable, and can alarm incessant to send signal
- Communication: RS485 or TCP/IP
- Other input: one group door magnet and door open signal input
- LCD, voice and keypad: four lines blue LCD, double LED indicator light, multi-language, 16 no. keypad
- Battery Supplier parameter: 12VDC, sleeping current<50mA, working current<400mA
- Operating: temperature, 0°C-65°C; humidity, 10%-90%
- Language: Multi-language optional
- Software: Professional access control software
- Support Wiegand out



SC302/3



SC402/3

Technical Specifications - SC103/203/303/403

- CPU: 32bit embedded RISC
- Capacity: 30000 card handle, 50000 logs
- Verified by: Card, Password+ Card, Pass word
- Reader interface/Data format: embedded 10cm proximity reader/26 bit wiegand. External carder reader interface/26 bit wiegand
- Access control function: 50 time zones, 5 groups, 10 combinations, support many cards access, 10A/12VDC relay switch volume or voltage output
- Alarm function: tamper alarm, threaten alarm, unlock illegally alarm, not block alarm. External alarmed speaker, alarmed light or alarm host connectable, and can alarm incessant to send signal
- Communication: RS485 or TCP/IP
- Other input: one group door magnet and door open signal input
- LCD, voice and keypad: four lines blue LCD, double LED indicator light, multi-language, 16 no. keypad
- Battery Supplier parameter: 12VDC, sleeping current<50mA, working current<400mA
- Operating: temperature, 0°C-65°C; humidity, 10%-90%
- Language: Multi-language optional
- U-Disk: 1G
- Software: Professional access control software
- Support Wiegand out and Wiegand in